



Model		ACAD 12V 10A	ACAD 24V 5A
OUTPUT	DC voltage	12V	24V
	Rated current	10A	5A
	Current range	0-10A	0-5A
	DC power	120W	120W
	Ripple and noise	100mVp-p	100mvp-p
	Intet stability	±0.5%	±0.5%
	Load stability	±1%	±1%
INPUT	Voltage range	AC100~240V 47~63Hz	
	Efficiency	77%	
	Leakage current	< 0.5mA/240VAC	
PROTECTION	Over load	105%~150% Type:pulsing hiccup shutdown Resete:auto recovery	
	Over voltage	13.8~16.2V	28.8-33.6V
		200ms,100ms,30ms	
SAFETY	Setup,rise,hold up time	200ms,100ms,30ms	
	Vibration	10~500Hz,2G 10min,/1 cycle	
	Withstand voltage	Input and output internal:1.5KvAc,input and enclosure:1.5KvAc,Output and enclosure:0.5KvAc	
	Isolation resistance	Input and output internal:Input and enclosure,Output and enclosure:500VDC/100MΩ	
ENVITONMENT	Temperature coefficient	±0.03%/°C (0~50°C)	
	Working temperature and humidity	-10°C ~+60°C,20%~90%RH	
	Store temperature and humidity	-20°C ~+85°C,10%~95%RH	
OTHERS	Overall dimension	129*55*29 mm	
	Weight	0.6Kg	
CERTIFICATE	CE EMC Authenticate	EN55022:2010 EN61000-3-2:2006+AL:2009 EN61000-3-3:2008	
		EN55024:2010 EN55015:2006+AL2007+2009 EN61547:2009	