



Model		ACAD BUPS 12V8A	ACAD BUPS 24V4A
OUTPUT	DC voltage	CH1:13.8V	CH1:27.6V
	Voltage tolerance	±1%	±1%
	Rated current	8A	4A
	Current range	0~8A	0~4A
	Rated power	117.1W	118.4W
	Ripple&noise	120mvp-p	180mvp-p
	DCvoltage ADJ.range	CH1:11.3~14.9V	CH1:21.3~29.8V
INPUT	Voltage range	90~264VAC,127~370VDC	
	Frequency	47~63HZ	
	AC current	2.8A/115VAC,1.4A/230VAC	
	Efficiency	81%	83%
	Inrush current	Cold start current 30A/115VAC,50A/230VAC	
	Leakage current	< 1mA/240VAC	
PROTECTION	Over load	Rated output power110%~150% start over load protection protection mode: AC charging mode:hiccup mode auto-recovery after fault condition is removed	
	Battery protection	9.5~11V	20~22V
	At low voltage	protection mode:cutoff output	
FUNCTION	UPS introduction	long-term online floating charge to battery, high charging efficiency, battery can saturate to more than 90% ,cauto-stop harging when it's full,prevent over charging. Effectively extend battery life,AC/battery auto switch,no switch time,no need human guard,	
		cold-start ,when there is no AC input ,can use battery start UPS, Meet the user's emergency needs	
ENVITONMENT	Working temp,humidity	-10°C~+60°C,20%~90%RH	
	Storage temp,humidity	-20°C~+85°C,10%~95%RH non-condensing	
	Withstand vibration	10~500HZ,2G 10min/1 cycle,period for 60 minutes,each axes	
SAFETY	Withstand voltage	I/P-O/P:3KVAC I/P-FG:1.5KVAC O/P-FG:0.5KVAC	
	Isolated resistance	I/P-O/P,I/P-FG,O/P-FG:100Mohms/500VDC	
OTHERS	Dimension	159 * 97 * 38mm (L*W*H)	
	Weight/packing	0.56kg/45pcs/26kg/0.041m 3;/1.45CUFT	